

TRINITY HOSE HOBBLE STRAP

Protect People, Property and Profits on the Pad with Trinity Sling's Hose Hobbles

Trinity's Hose Hobbles Are:

- Made from strong, durable polyester webbing
- Designed for easy use on water, hydraulic and pneumatic hoses.
- Available in Various Standard Lengths
- Designed to fit hoses with inside diameters from 1/4" to 6"
- Easily Adjustable

Trinity's Hose Hobbles satisfy the requirements for restraining hose connections mandated by the following workplace safety organizations:

- OSHA
- Canada OHS
- WorkSafe BC



OSHA 1926.603(A)(10)

"Safety chains, or equivalent means, shall be provided for each hose connection to prevent the line from thrashing around in case the coupling becomes disconnected."

Trinity Sling | 3508 Avenue F East, Arlington, TX 76011 | 877-589-2404 | www.trinitysling.com



TRINITY HOSE HOBBLE STRAP

Hose ID (in)	Max Internal Pressure (PSI)
1/4	52,000
1/2	13,000
3/4	5,800
1	3,300
2	750
3	350
4	200
5	125
6	90

Part No.	Hose ID(in)	Strap Length
TSH2-30	1/4" TO 2"	30"
TSH2-44	1" TO 4"	44"
TSH2-64	2" TO 6"	64"



OSHA 3763-12 2014

"Restrain or secure high pressure lines including relief lines with proven restraint devices and methods to prevent potential 'whipping' of these lines should there be an equipment failure."

Trinity Sling | 3508 Avenue F East, Arlington, TX 76011 | 877-589-2404 | www.trinitysling.com